

Versilon® G-FDA Hose

HIGH-TEMPERATURE SUCTION AND DISCHARGE RUBBER HOSE

Versilon® G-FDA hose is built for higher temperatures and more chemically demanding applications. It boasts our highest temperature rating for any non-fluoropolymer lined rubber covered hose.

The non-PVC, non-butyl, all EPDM liner is designed to reduce the risk of taste and odor adulteration of food. A robust dual-helix wire reinforcement allows the EPDM liner to withstand full vacuum, making it the best EPDM lined hose for suction and discharge service.

Typical Applications

- Cosmetics
- High purity water
- Bulk food transfer
- Beverage
- Dairy
- CIP applications

Features and Benefits

- Sanitary suction and discharge hose
- White EPDM liner
- EPDM cover and reinforcements designed to withstand rough handling and high temperatures
- Full vacuum rating
- Food oil and ozone resistant
- Custom laylines available
- Specially designed to handle oil based materials
- Designed to reduce risk of taste and odor adulteration of food

Regulatory Compliance

- Compliant with FDA 21CFR 177.2600
- USDA
- 3-A Sanitary Standard 62-02



Versilon® G-FDA Hose

Versilon® G-FDA Hose Specifications

Part Number	Inside Diameter		Outside Diameter		Maximum Working Pressure*		Minimum Burst Pressure		Minimum Bend Radius**		Vacuum Hg		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(MPa)	(psi)	(MPa)	(in)	(mm)	(in)	(mm)	(lb/ft)	(kg/m)
GFDA-0500	0.50	12.7	0.98	24.9	150	1.03	600	4.14	2.50	63.5	29.9	760	0.30	0.45
GFDA-0750	0.75	19.1	1.27	32.3	150	1.03	600	4.14	3.75	95.3	29.9	760	0.44	0.65
GFDA-1000	1.00	25.4	1.50	38.1	150	1.03	600	4.14	4.00	101.6	29.9	760	0.57	0.85
GFDA-1500	1.50	38.1	2.09	53.1	150	1.03	600	4.14	5.00	127.0	29.9	760	0.91	1.35
GFDA-2000	2.00	50.8	2.63	66.8	150	1.03	600	4.14	6.00	152.4	29.9	760	1.30	1.93
GFDA-2500	2.50	63.5	3.17	80.5	150	1.03	600	4.14	7.00	177.8	29.9	760	1.74	2.59
GFDA-3000	3.00	76.2	3.72	94.5	150	1.03	600	4.14	8.00	203.2	29.9	760	2.42	3.60
GFDA-4000	4.00	101.6	4.78	121.4	150	1.03	600	4.14	11.00	279.4	29.9	760	3.22	4.79

NOTE: Weights and outside diameter dimensions are nominal. Data given is for hose only. End fitting vs. hose pressure limitations must be considered and the lower of the two ratings must be used on assemblies.

* Based on ambient condition on exterior of hose. Elevated temperatures and characteristics of medium being transferred can affect working pressures and burst pressures.

** Measured on the inner surface of the curved portion. Data is based on static applications. For dynamic or cyclic applications, consult factory.

Construction

Inner Tube:	Seamless white EPDM			
Cover:	EPDM			
Reinforcement:	Two fabric spirals with dual helix wire			
Color:	Gray with a white layline in blue lettering			
Temperature Rating:	-40°F to +300°F -40°C to +149°C			
Maximum Length:	1/2"	60'	2"	60'
	3/4"	60'	2-1/2"	50'
	1"	60'	3"	60'
	1-1/2"	60'	4"	60'

Fitting Options

Versilon® Crimp Style Fittings

- Over 40 styles of stocked crimp-style fittings in a wide range of materials
- Standard: 316L stainless steel (wetted surfaces)

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

www.ics.saint-gobain.com



Saint-Gobain
210 Harmony Road
Mickleton, NJ 08056
USA



NOTE: The data and details given in this document are correct and up to date. This document is intended to provide information about the product and possible applications. This document is not the product specification and does not provide specific features, nor does it guarantee product performance in specific applications. Saint-Gobain cannot anticipate or control the conditions of the field and for this reason strongly recommends that practical tests are conducted to ensure that the product meets the requirements of a specific application.

Versilon® is a registered trademark of Saint-Gobain Performance Plastics Corporation.