



Versilon® TB Hose


STAINLESS STEEL BRAIDED SMOOTH INNER TUBE ANTI-STATIC FLUOROPOLYMER HOSE

Saint-Gobain's Versilon® TB hose is constructed with a black electrostatic dissipating conductive PTFE smooth inner tube and reinforced with 304 stainless steel braid. TB hose is designed with up to a 33% thicker PTFE inner tube versus competitive hoses. This characteristic enables smooth tube hoses to have superior kink resistance, improved vacuum ratings and higher resistance to damage.

Versilon® TB hose is designed with a full size internal diameter to maximize the flow rate, providing greater transfer speed when compared with similar products that only come with a tube size internal diameter. TB hose is engineered to reduce the pressure drop through the fitting area, ensuring a longer service life. TB hose cleans easily with steam, detergent or caustic and can be autoclaved. It is also non-stick and non-contaminating.

Typical Applications

- Compressed gas transfer
- Compressed gas cylinder filling
- Sanitary fluid transfer
- Steam transfer
- Gas analysis
- Hydraulic lines
- Extrusion presses
- Injectable material and adhesive conveying



Features and Benefits

- Greater wall thickness of PTFE tube
 - Up to 33% thicker than competing products (tube wall .040 minimum)
 - Superior kink resistance
 - Improved vacuum ratings
 - Better damage resistance
- Non-sticking, non-contaminating
- Cleans easily via steam, detergent or caustic
- Can be autoclaved
- Full ID sizes
 - Greater flow rate per given size
 - Less pressure drop through fitting area than hoses with tube size ID

Regulatory Compliance

- US Pharmacopeia Class VI



Versilon® TB Hose

Versilon® TB Hose Specifications

Part Number	Inside Diameter		Outside Diameter		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Vacuum Hg @ 70°F		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(MPa)	(psi)	(MPa)	(in)	(mm)	(in)	(mm)	(lb/ft)	(kg/m)
1604TB400	1/4	6.4	3/8	9.5	3,000	20.68	12,000	82.74	2.00	50.8	29.9	760	0.08	0.12
1606TB400	3/8	9.5	1/2	12.7	2,500	17.24	10,000	68.95	4.50	114.3	29.9	760	0.12	0.18
1608TB400	1/2	12.7	5/8	15.9	2,000	13.79	8,500	58.61	5.00	127.0	29.9	760	0.15	0.22
1612TB400	3/4	19.1	7/8	22.2	1,200	8.27	4,800	33.09	9.00	228.6	29.9	760	0.27	0.40
1616TB500	1	25.4	1-1/8	28.6	800	5.52	3,500	24.13	12.00	304.8	20.0	508	0.35	0.52
1624TDB60	1-1/2	38.1	1-3/4	44.5	900	6.21	3,600	24.82	18.00	457.2	15.0	381	0.79	1.18

NOTE: Weights and outside diameter dimensions are nominal. Data given is for hose only. End fitting vs. hose pressure limitations must be considered and the lower of the two ratings must be used on assemblies.

! Important:

Burst pressure ratings at ambient 70°F (21°C). See applicable notes below on vacuum pressure ratings at temperatures other than ambient.

Working Pressure is given at 70°F; decrease working pressure 1% for every 2°F above 350°F. 1-1/2" size (TDB) vacuum rating decreases when installed less than 2X minimum bend radius.

Vacuum Rating is given at 70°F; decrease vacuum rating 1% for every 2°F above 350°F. 1-1/2" size (TDB) vacuum rating decreases when installed less than 2X minimum bend radius.

Extended Service Life Tip: All 3/4", 1" and 1-1/2" TB/TDB assemblies 36" and longer are strongly recommended to use full-length anti-kink casing and/or liner vacuum collapse.

Construction

Inner Tube:	Black electrostatic dissipating conductive PTFE																
Reinforcement:	304 stainless steel braid 1-1/2" ID size double-braided for added kink resistance, higher pressure rating; working pressure based on minimum 4:1 safety factor; burst to suggested maximum working pressure																
Temperature Rating:	-100°F to +450°F (continuous) +500°F (intermittent) -73°C to +232°C (continuous) +260°C (intermittent)																
Minimum Overall Length of Hose Assemblies with Anti-Kink Casing:	1/4" size - 18" OAL 3/8" and 1/2" sizes - 24" OAL																
Average Length:	<table border="1"> <tr> <td>1/8"</td> <td>50'</td> <td>3/4"</td> <td>40'</td> </tr> <tr> <td>1/4"</td> <td>125'</td> <td>1"</td> <td>30'</td> </tr> <tr> <td>3/8"</td> <td>75'</td> <td>1-1/2"</td> <td>30'</td> </tr> <tr> <td>1/2"</td> <td>125'</td> <td></td> <td></td> </tr> </table>	1/8"	50'	3/4"	40'	1/4"	125'	1"	30'	3/8"	75'	1-1/2"	30'	1/2"	125'		
1/8"	50'	3/4"	40'														
1/4"	125'	1"	30'														
3/8"	75'	1-1/2"	30'														
1/2"	125'																

Fitting Options

Versilon® Crimp Style Fittings

- Over 40 styles of stocked crimp-style fittings in a wide range of materials
- Standard: 316L stainless steel (wetted surfaces)

Common Media

- Chemicals
- Steam
- Solvents
- Inks and dyes
- Paint
- Injectable materials
- Plastisols

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Saint-Gobain
210 Harmony Road
Mickleton, NJ 08056
USA

www.ics.saint-gobain.com



NOTE: The data and details given in this document are correct and up to date. This document is intended to provide information about the product and possible applications. This document is not the product specification and does not provide specific features, nor does it guarantee product performance in specific applications. Saint-Gobain cannot anticipate or control the conditions of the field and for this reason strongly recommends that practical tests are conducted to ensure that the product meets the requirements of a specific application.

Versilon® is a registered trademark of Saint-Gobain Performance Plastics Corporation.